



SPARK PLUG

Patent number: JP11339925
Publication date: 1999-12-10
Inventor: NISHIKAWA KENICHI; TANAKA MINORU
Applicant: NGK SPARK PLUG CO
Classification:
- international: **H01T13/34; H01T13/41; H01T13/00; H01T13/20; (IPC1-7): H01T13/20**
- european: **H01T13/34; H01T13/41**
Application number: JP19980144596 19980526
Priority number(s): JP19980144596 19980526


Also published as:

 EP0961373 (A1)
 US6188166 (B1)

Report a data error here

Abstract of JP11339925

PROBLEM TO BE SOLVED: To provide a spark plug having a structure in which a joining force between a conductive glass seal layer and a terminal fitting can be enhanced and which hardly generates an inconvenience such as dropping off of the terminal fitting and a deterioration of a joining state between the terminal fitting and the conductive glass seal layer. **SOLUTION:** In a spark plug 100 having a resistor, a terminal fitting 13 is fixed to one end side against a through hole 6 axially formed on an insulator 2 and a center electrode 3 is fixed to the other end side. Then, conductive bonding layers 17, 15, 16 are disposed between the terminal fitting 13 and the center electrode 3 in the through hole 6. Further, a seal 13c of the terminal fitting 13 is joined to the resistor 15 through the conductive glass seal layer 17 and a surface layer area is made of a metal layer having one kind or two kinds of Zn, Sn, Pb, Rh, Pd, Pt, Cu, Au, Sb and Ag as a main component.



Data supplied from the esp@cenet database - Worldwide